



# MATERIAL SAFETY DATA SHEET

## BRITE WHEELS

### SECTION 1 – IDENTIFICATION

**Product Name** Brite Wheels  
**Recommended Use** Mag Wheel Cleaner  
**Supplier** TASMAN CHEMICALS PTY LTD  
**ACN :** 005 072 659  
**Street Address** 1-7 Bell Grove, Braeside ,  
Victoria 3195 AUSTRALIA  
**Telephone Number** (03) 9587 6777  
**Facsimilie** (03) 9587 5255  
**Email** taschem@taschem.com.au  
**Website** www.tasmanchemicals.com.au  
**Emergency Telephone Number** 1 800 334 556

### SECTION 2 – HAZARDS IDENTIFICATION

#### Hazardous according to criteria of Safe Work Australia.

Hazard Category : Xn ( Harmful ), C (Corrosive)

#### Risk Phrases

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.  
R36/37/38 Irritating to eyes, respiratory system and skin

#### Safety Phrases

S1/2 Keep locked up and out of the reach of children  
S24/25 Avoid contact with skin and eyes  
S26 In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or the Poisons Information Centre.  
S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
S45 In case of accident or if you feel unwell, seek medical advice immediately ( show the label wherever possible )

**Brite Wheels** is classified as **Dangerous Goods Class 8** according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

### SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

| <u>Ingredient</u>    | <u>CAS Number</u> | <u>Proportion (%m/m)</u> |
|----------------------|-------------------|--------------------------|
| Water                | 7732-18-5         | VH                       |
| Oxalic Acid          | 144-62-7          | M                        |
| Monoethanolamine     | 141-43-5          | L                        |
| Non Ionic Surfactant | 9016-45-9         | L                        |
| Perfume              | Proprietary       | L                        |
| Dye                  | Proprietary       | L                        |

**VH>60% H>30-60% M=10-30% L=<10%**

## SECTION 4 – FIRST AID MEASURES

### First Aid

- Swallowed: If swallowed **DO NOT** induce vomiting. Give a 1-3 glasses of water to drink. Seek immediate medical assistance or contact the Poisons Information Centre immediately.
- Eye: If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek immediate medical assistance or contact the Poisons Information Centre immediately.
- Skin: If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water.
- Inhaled Remove victim from further exposure. Remove contaminated clothing and loosen remaining clothing. If NOT breathing, apply artificial resuscitation. If breathing difficult administer oxygen. Allow patient to assume most comfortable position. Seek medical attention if effects persist.

**Advice to Doctor** Treat symptomatically.

## SECTION 5 – FIRE FIGHTING MEASURES

### Fire/Explosion Hazard

This material is not combustible under normal conditions. However, it can react with certain metals to produce flammable hydrogen gas. On burning will emit toxic fumes. Fire fighters should wear self-contained breathing apparatus if risk of exposure to vapour or products of combustion. Keep containers cool by spraying with water to prevent pressure building up inside the drums, causing them to burst.

### Extinguishing Media

Use water spray, 'alcohol' foam, dry chemical or carbon dioxide. Avoid using large quantities of water.

## SECTION 6 – ACCIDENTAL RELEASE MEASURES

### Spills

Increase ventilation. Wear protective equipment to prevent skin and eye contamination and inhalation of vapours or mists. Contain using sand or soil – prevent run off into drains and waterways. Use absorbent (soil, sand vermiculite or other inert material). Neutralise with lime or soda ash. Collect and seal in properly labelled drums for disposal. If contamination of sewers or waterways has occurred advise local emergency services.

## SECTION 7 – HANDLING AND STORAGE

**Handling** : Avoid skin and eye contact

**Storage** : Under normal weather conditions store in a well-ventilated area.  
Store in a dry cool environment  
Keep containers closed at all times when not in use.  
Store away from alkalis or chlorine compounds  
Check regularly for leaks. Remove drum bungs slowly to release any internal pressure.

## SECTION 8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Occupational Exposure Limits** : Threshold Limit Values for Oxalic Acid

Time Weighted Average ( TWA ) = 1 mg/m<sup>3</sup>  
Short Term Exposure Limit ( STEL ) = 2 mg/m<sup>3</sup>

Exposure Standards (TWA) is the time-Weighted average airborne concentration over an eight-hour working day, for a five day working week over an entire working life. According to current knowledge this concentration should neither impair the health or, cause undue discomfort to, nearly all workers.

STEL (Short Term Exposure Limit): the average airborne concentration over a 15 minute period that should not be exceeded at any time during a normal eight-hour work day.

NOTICE : Absorption through the skin may be a significant source of exposure

**Engineering Control Measures** : Ensure ventilation is adequate to maintain air concentrations below recommended exposure standard. Keep containers closed when not in use

### **Personal Protective Equipment** :

Eye: Safety Glasses

Hands: Impervious plastic or rubber gloves.

Other: Not applicable

Respirator: Dust Mask

Always wash hands before eating, drinking, smoking or using the toilet.

Wash contaminated clothing and other protective equipment before storage and reuse.

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

|                   |                               |                   |                |
|-------------------|-------------------------------|-------------------|----------------|
| Appearance/Odour: | Clear Green Liquid            | pH (as is):       | 1 to 3         |
| Melting Point:    | 0oC                           | Flash Point:      | Not applicable |
| Boiling Point:    | 100°C (approximately)         | Volatiles         | Water only     |
| Density: @ 25°C   | 1.08 grams/mL (approximately) | Flammable Limits: | Not applicable |
| Solubility:       | Miscible                      |                   |                |

## SECTION 10 – STABILITY AND REACTIVITY

**Stability** Incompatible with alkalis and strong oxidising agents

**Reactivity** May react with strong oxidants. Toxic gases and vapours may be released

## SECTION 11 – TOXOLOGICAL INFORMATION

### **Health Effects**

No adverse health effects expected if the material is handled in accordance with the Material Safety Data Sheet. Symptoms that may arise if the material is mishandled are :

### **Acute Effects**

Swallowing: May cause severe pain and burning of the mouth & oesophagus, nausea, vomiting & Diarrhoea. Oral LD50 = 475 mg/kg ( Rat ) – Oxalic Acid

Eye: A severe eye irritant. May cause severe eye damage

Skin: Contact with skin will result in severe irritation. Repeated or prolonged skin contact may cause burns and permanent damage.  
Dermal LD50 = 20000 mg/kg ( rabbit ) – Oxalic Acid

Inhaled: Vapour or mist may be irritant to mucous membranes and respiratory tract

**Chronic Effects**

Principal routes of exposure are by accidental skin or eye contact  
Prolonged or repeated skin contact may have a corrosive action on human tissues

**SECTION 12 – ECOLOGICAL INFORMATION**

Avoid contaminating waterways. Spills should be contained, absorbed by sand or earth and placed in sealed plastic or epoxy-lined drums for disposal

**SECTION 13 – DISPOSAL CONSIDERATIONS**

Refer to Waste Management Authority .

**SECTION 14 – TRANSPORT INFORMATION**

Classified as a Dangerous Good by the Criteria of the Australian Dangerous Good Code

|                        |                               |                         |    |
|------------------------|-------------------------------|-------------------------|----|
| Proper Shipping Name : | Corrosive Liquid, Toxic N.O.S |                         |    |
| UN Number :            | 2922                          | Dangerous Goods Class : | 8  |
| Subsidiary Risk :      | Not applicable                | Hazchem Code :          | 2X |
| Packing Group :        | III                           |                         |    |

**SECTION 15 – REGULATORY INFORMATION**

**Classification** Based upon information, classified as hazardous according to criteria of Safe Work Australia

**Poisons Schedule** Schedule 6

**SECTION 16 – OTHER INFORMATION**

Contact Points

| <u>Organisation</u>        | <u>Location</u>                     | <u>Telephone</u> | <u>Ask For</u>    |
|----------------------------|-------------------------------------|------------------|-------------------|
| Tasman Chemicals Pty Ltd   | Braeside,<br>Victoria,<br>Australia | (03) 9587 6777   | Technical Manager |
| Poisons Information Centre |                                     | 13 1126          |                   |

MSDS are updated frequently. Please ensure that you have a current copy.

*This MSDS summarises our best knowledge of the health and safety hazard information of the product; how to safely handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Tasman Chemicals Pty Ltd. Our responsibility for products sold are subject to our standard terms and conditions, a copy of which appears on all invoices. It is also available on request. Where health or safety data given discloses a risk to the user or environment, it is the responsibility of the Purchaser to pass on that information to employees or those who may be using the product, ensuring that adequate safety procedures are used including good industrial hygiene.*