



Product Information Sheet

Re-Issue Date: 06/01/05

Page 1 of 2

PORCELAIN SEALER

PENETRATING SEALER FOR PORCELAIN & NATURAL STONE

DESCRIPTION

PORCELAIN SEALER is a clear, water white liquid based on a blend of silanes and siloxanes in a low odour solvent.

APPLICATION

PORCELAIN SEALER is a natural look penetrating sealer specifically designed for the sealing of very dense tiles, stone and grout including porcelain, polished marble, polished granite, terrazzo, vitreous tile and cement grout. PORCELAIN SEALER is suitable for use both internally and externally and will inhibit the majority of soiling and staining of the tile.

FEATURES	BENEFITS
○ Low Odour	○ No lingering unpleasant odours, especially in indoor applications.
○ Versatile	○ Suitable for both indoor and outdoor applications.
○ Economical	○ Only one coat is required to provide complete protection.
○ Extremely Effective	○ Will inhibit a broad range of stains including tea, coffee, beetroot, soft drinks and sauces.

DIRECTIONS FOR USE

1. In order to determine the compatibility of PORCELAIN SEALER with your floor, a test area of at least four tiles, and waiting 24 hours to assess before proceeding to seal the entire floor. If the finish in this area meets with your requirements continue to seal the remaining tiles.
2. Surface to be sealed must be completely clean and dry – free from grease, oil, paint, acid, efflorescence and traces of grout.
3. Newly laid areas need approximately 7 days to allow mortar and grout to cure and dry prior to sealing.
4. Any stains and soiling or old sealer on the tiles must be removed prior to sealing by using a suitable detergent and a stripper.
5. Allow the tiles to dry thoroughly prior to sealing by leaving for at least 24 hours after cleaning and washing.
6. Do not seal hot surfaces – all surfaces must be cool.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied. 1

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413



Product Information Sheet

PORCELAIN SEALER

Re-Issue Date: 06/01/05

Page 1 of 2

7. PORCELAIN SEALER is applied neat. (a) Using a clean brush apply a light, even, continuous coat. (b) Allow 2 hours for the surface to dry. Buff the surface with a single-disc professional polisher fitted with a white or beige disc or a household polisher fitted with felt pads or buff with a dry cloth. (c) Any excess due to over-application can be removed with a cloth dipped in Slate Seal Solvent, this allows the excess to be re-spread and removed simultaneously, so the floor is ready for use at once. (d) Re-apply PORCELAIN SEALER when beading of liquids on the surfaces diminishes.
8. One litre will cover approximately 50m² dependant upon the porosity of the tiles.
9. If you have any queries about the use of the product please contact our Technical Services Department at Tasman Chemicals or visit our website:
www.tasmanchemicals.com.au
10. We recommend the use of Tasman Tile Kleen to maintain your floor.
 - Any spills should be removed immediately to minimise absorption. Some drinks and foods are acidic and to avoid etching should be removed quickly.

CLEAN UP

Brushes must be cleaned with Tasman Slate Seal Solvent or softened by soaking in PORCELAIN SEALER 10 minutes prior to reapplication.

PACKAGING

- ◆ 1 LT Metal Tin
- ◆ 4 LT Metal Tin
- ◆ 10 LT Metal Tin
- ◆ 20 LT Metal Tin

HEALTH AND SAFETY INFORMATION

See separate Material Safety Data Sheet available on request.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

2

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Tasman Chemicals Pty Ltd

Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413