



## Product Information Sheet

Re-Issue Date: 01/04/03

Page 1 of 2

### PRE SEAL

#### DESCRIPTION:

PRE SEAL is an opaque solution designed for application to a wide variety of porous surfaces in order to protect those surfaces from staining, soiling and discolouration of tiles prior to sealing.

#### APPLICATION:

Suitable for commercial and domestic areas on the following materials.

- ⇒ Terracotta
- ⇒ Sandstone
- ⇒ Limestone
- ⇒ Quarry Tiles

#### BENEFITS:

- PRE SEAL allows easy removal of grout prior to sealing.
- Helps to prevent staining, soiling and discolouration of tiles caused by most common soils and food residues.
- Suitable for a wide variety of porous substrates such as terracotta, sandstone and limestone.

#### DIRECTIONS FOR USE:

1. In order to determine the compatibility of PRE SEAL with the surface you are going to seal, a test area of one or two tiles should be attempted before sealing the entire area. If the finish in this area meets your requirements continue to seal the remaining tiles.
2. Surface to be sealed must be clean and dry, free from grease, oil, paint, acid and efflorescence.
3. Prior to sealing the surface to be sealed should be cleaned with Tasman's TILE KLEEN. Allow at least 24 hours for the cleaned area to dry.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

#### *Tasman Chemicals Pty Ltd*

*Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255*

*New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647*

*South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622*

*Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989*

*Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511*

*Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413*



## Product Information Sheet

**PRE SEAL**

**Page 2 of 2**

4. Apply PRE SEAL neat using a clean paint brush or sponge. Allow 5-10 minutes to penetrate the surface then wipe off excess with damp sponge. (PRE SEAL should not be applied to any surface when the temperature is less than 10°C).
5. For very porous tiles, such as sandstone, Mexican or Spanish terracotta, a second application may be required. Allow 4 hours between each application.
6. Avoid heavy traffic and contamination from moisture for 24 hours after sealing.
7. For regular cleaning of tiles use TILE KLEEN as a maintenance cleaner.
8. After waiting a suitable period of time apply HERITAGE FINISH or TERRACOTTA SEAL as per instructions depending on the type of finish required.
9. As this product is used under conditions beyond our control, the seller will not be responsible for results obtained. Liability is restricted to the replacement of any material faulty and the manufacturer is not responsible for any loss or damage arising from incorrect usage.
10. Determining the suitability of the product for any intended usage shall be the sole responsibility of the user.

Coverage: 1 litre will cover 10-15 square metres depending on the porosity of the tiles.

### **CLEAN UP:**

Brushes and application equipment may be cleaned with a hot solution of TILE KLEEN.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

#### ***Tasman Chemicals Pty Ltd***

***Victoria:*** 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

***New South Wales:*** Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

***South Australia:*** 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

***Tasmania:*** 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

***Western Australia:*** 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

***Queensland:*** Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413