



## Product Information Sheet

Re-Issue Date: 01/12/04  
Page 1 of 2

### SLATE SEAL

#### DESCRIPTION

Tasman SLATE SEAL Gloss or Satin is a clear solvent based acrylic sealer. It has been UV stabilised to ensure your slate has the best possible protection against the sun's harmful rays. Tasman SLATE SEAL is suitable for both commercial and domestic slate areas, unglazed terracotta, quarry tiles, paving bricks, most interior and exterior applications, such as kitchens, family rooms, hearths, bathrooms, shower recesses, patios and pool surrounds.

Tasman SLATE SEAL will prevent staining and allow low cost maintenance with NO STRIPPING ever. To reseal or touch-up, simply cover worn areas as needed.

Note: Newly laid areas need approximately 2-4 weeks to allow mortar and grout to cure and dry prior to sealing (depending on weather conditions).

#### DIRECTIONS FOR USE

**WARNING:** Ensure good ventilation to dispense solvent vapours. Keep away from naked flames, etc.

1. Surface to be sealed must be thoroughly clean and dry - free of grease, oil, paint, acid, efflorescence, loose flakes of slate and traces of grout.
2. Prior to sealing allow cleaned area to dry for at least 24 hours (depending on weather conditions).
3. Surfaces previously sealed with slate sealers other than Tasman Slate Seal, must have all traces of old sealer and polish completely removed with suitable strippers. Surfaces polished with Tasman Slate Finish must be stripped with Tasman Ripper Stripper.
4. Do not seal hot surfaces - all surfaces must be cool.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

#### *Tasman Chemicals Pty Ltd*

*Victoria: 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255*

*New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647*

*South Australia: 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622*

*Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989*

*Western Australia: 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511*

*Queensland: Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413*



## Product Information Sheet

SLATE SEAL

Page 2 of 2

5. Tasman SLATE SEAL is applied neat using a clean paint brush or lambswool applicator. If using a roller, ensure air bubbles are not induced in the wet film, which may remain after seal has dried. To avoid the collection of puddles, work in small areas applying two thin coats of Tasman SLATE SEAL allowing not less than 4 hours between coats.
6. Full curing will take up to 24 hours and traffic should be restricted as much as possible during this time. However, surfaces may be lightly walked upon after 2 hours.
7. Brushes may be cleaned in Tasman SLATE SEAL SOLVENT or softened by soaking in Tasman SLATE SEAL 10-15 minutes prior to use.

DO NOT USE MINERAL TURPENTINE ETC. UNDER ANY CIRCUMSTANCES.

8. To maintain your seal in dry heavy traffic areas use Tasman SLATE FINISH.

### **COVERAGE:**

1 litre will cover approximately 8-10m<sup>2</sup> with two coats.

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

**Tasman Chemicals Pty Ltd**

**Victoria:** 1-7 Bell Grove, Braeside 3195 Ph: 61-3-9587 6777 Fax: 61-3-9587 5255

**New South Wales:** Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

**South Australia:** 4/159 Williams Street, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

**Tasmania:** 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

**Western Australia:** 8 O'Connor Way, Wangara 6065 Ph: 61-8-9309 2100 Fax: 61-3-9309 2511

**Queensland:** Unit 12/172 Redland Bay Road, Capalaba, 4157 Ph: 61-7-3245 2862 Fax: 61-7-3245 2413