



Product Information Sheet

Issue Date: 01/08/05
Page 1 of 2

SPRAY SEAL

TILE , STONE & GROUT SEALER

DESCRIPTION

SPRAY SEAL is an aerosol that penetrates into tiles and grout making them water repellent without providing a slippery surface.

APPLICATIONS

Spray Seal can be used to seal the following surfaces:

- Shower mortar & grout
- Quarry tiles
- Sandstone
- Terracotta
- Stone
- Limestone
- Porcelain

BENEFITS

- Quickly penetrate surface
- Inhibits stain absorption
- Leaves Natural Appearance
- Easy spray application
- Simple and safe to use
- Non Yellowing, UV Resistant

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 2-6 Roberna Street, Moorabbin 3189 Ph: 61-3-9555 8033 Fax: 61-3-9553 2902

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Road, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: Unit 1/22 Industry Street, Malaga, 6090 Ph: 61-8-9248 9711 Fax: 61-8-9249 9183

Queensland: 109 Boundary Road, Thornlands 4164 Ph: 61-7-3206 3427 Fax: 61-7-3206 3644

New Zealand: Tasman Chemicals Ltd, PO Box 100-761, North Shore Mail Centre, Auckland Ph: 64-9-444 4401 Fax: 64-9-444 4839



Product Information Sheet

Issue Date: 01/08/05

Page 1 of 2

DIRECTIONS FOR USE

1. Prior to sealing with Spray Seal ensure that the surface is thoroughly cleaned and dry and free from grease, oil, paint, acid, efflorescence and traces of grout
2. Leave area to dry for a minimum of 24 hours prior to sealing.
3. Fix all missing or broken tiles prior to sealing.
4. Do a test area to see if compatible with surface to be sealed.
5. Hold spray can approximately 15 –20 cm away from desired surface and spray in a sweeping action. Allow 5 – 10 minutes to penetrate the surface then wipe off excess with damp cloth
6. A second application may be applied after another four hours
7. Allow 24 hours for product to cure after sealing.

COVERAGE

One can will cover approximately 25m² or 600 linear metres of grout lines dependent on porosity of the surface being treated and grout line width.

NOTE

Spray Seal should last up to 2 years, depending on the type of cleaning products used on the sealed area. Tasman recommend Bathroom Magic as an all purpose cleaner/sanitiser. Spray Seal can be used interior or exterior.

PACKAGING

300 gm aerosol - 12 per carton.

HEALTH AND SAFETY INFORMATION

See Separate Material Safety Data Sheet available on request

The Product Information Sheet supersedes all previous issues for this product. Information contained herein is offered in good faith as being true and accurate to the best of our knowledge, but as the conditions of use are beyond our control, no guarantees are either stated or implied.

Where health or safety data given discloses a risk to the user or the environment, it is the responsibility of the purchaser to pass on the information to employees who may be using the product, ensuring that adequate safety procedures are used, including good industrial hygiene.

Australia: Tasman Chemicals Pty Ltd

Victoria: 2-6 Roberna Street, Moorabbin 3189 Ph: 61-3-9555 8033 Fax: 61-3-9553 2902

New South Wales: Suite 15, 380 Pennant Hills Road, Pennant Hills 2120 Ph: 61-2-9980 5999 Fax: 61-2-9484 8647

South Australia: 4/159 Williams Road, Beverley 5009 Ph: 61-8-8243 0644 Fax: 61-8-8243 0622

Tasmania: 1 Durham Road, Cooee 7320 Ph: 61-3-6432 1988 Fax: 61-3-6432 1989

Western Australia: Unit 1/22 Industry Street, Malaga, 6090 Ph: 61-8-9248 9711 Fax: 61-8-9249 9183

Queensland: 109 Boundary Road, Thornlands 4164 Ph: 61-7-3206 3427 Fax: 61-7-3206 3644

New Zealand: Tasman Chemicals Ltd, PO Box 100-761, North Shore Mail Centre, Auckland Ph: 64-9-444 4401 Fax: 64-9-444 4839